Heritage Series Standard Specifications

Floors

- 2x10 Floor Joists @ 16" O.C. with Double Perimeter Band Front and Rear (12" O.C. on 31'-6" Wide Models)
- ★ 5/8" T&G OSB Floor Decking Glued and Nailed
- ⋆ Vinyl Floor Covering (Per Plan)
- * 25 oz. FHA Approved Carpet with 8 lb. Rebound Pad (Per Plan)

Walls

- * 2x6 Exterior Walls @ 16" O.C. with 7/16" OSB Sheathing
- * 8" Mating Walls @ 16" O.C. with Sheathing
- * 2x4 Interior Walls @ 16" O.C.
- \star 1/2" Drywall Throughout, Glued and Screwed
- 🛦 8'-0" Wall Height

Roof

- 7/12 Pitch, Non-Storage Rafter Roof System @ 16" O.C.
- ★ 10" Gable End Overhangs
- \star 10" Eave Overhangs, Fixed with Soffit and Fascia Installed when Possible
- * 7/16" OSB Roof Sheathing
- Ice Shield Installed on Eave Overhangs
- * Minimum 15# Felt Paper Shingle Underlayment
- * Vented Vinyl Soffit, Ribbed Aluminum Fascia, and Aluminum Drip Edge
- * 30 Year Tamko Architectural Shingles
- Shingle Over Ridge Vent (Shipped Loose)

Insulation

- * R-21 Fiberglass Exterior Wall Insulation with Vapor Barrier
- * R-38 Ceiling Insulation with Vapor Barrier
- * Exterior House Wrap

Exterior

- 🙀 CertainTeed "Main Street" Vinyl Siding (Dbl 4 Clapboard, Dbl 5 Clapboard, or Dutch Lap)
- Smooth Fiberglass Front Door with Sunburst, Composite Jambs, and Vinyl Brickmould (Per Plan)
- * Smooth Fiberglass Rear Door with Half Glass, Composite Jambs, and Vinyl Brickmould (Per Plan)
- 6'-0" Vinyl Sliding Glass Door (Per Plan)
- 🔅 Satin Nickel Schlage Lever Locks Exterior Door Hardware and Dead Bolt Keyed Alike
- * Vinyl Double Hung Low "E" Brickmould Windows with Screens and Argon Gas
- ★ One Exterior Light Supplied for Each Door
- ★ Vinyl Shutters, Installed on Front
- * Exterior Doors Installed with Pan & Bracing Beneath Jamb

Interior

- ★ Warm Beige Primer Paint on Walls with 3-5/8" Crown Moulding, Throughout Living and Bedroom Areas
- * Smooth Ceilings with White Primer Paint
- 2-Panel Cathedral-Top Interior Doors with Smooth Finish
- Satin Nickel Lever Style Hardware
- * Privacy Hardware on Bathrooms and Master Bedroom
- * 3-1/2" Colonial Base Moulding and 2-1/4" Colonial Casing (Semi-Gloss White)
- ★ Windows Sills (Semi-Gloss White)
- ★ 16" Deep Linen and Pantry Shelving (4 Rows)
- * Shirt and Skirt Shelving for Walk in Closets

Cabinetry

- * Oak Recessed Flat Panel Kitchen Cabinets
- ★ 2-1/2" Crown Moulding and Under Cabinet Trim
- ★ Dove Tail Drawers, 3/4" Shelves with 1 Pull-Out Tray
- 🧩 75 lb. Full Extension Drawer Glides with Soft-Action Close Mechanism on Base Cabinet Drawers
- 🗴 Elevated Corner Wall Cabinet, Crown and Under Cabinet Trim
- High Pressure, Square Edge Laminate Top and Backsplash (Kitchen)
- * Oak Recessed Flat Panel Bath Cabinets

Cabinetry (cont)

- * One-Piece Cultured Marble Vanity Top (Baths)
- ★ Medicine Cabinet with Mirror and Decorative Lighting (Per Vanity Bowl)

Plumbing and Heating

- * Tuff-Pex Fresh Water Lines Stubbed (Code Dictates)
- * PVC Drain, Waste, and Vents (Stubbed)
- * Shut-Off Valves on All Fixtures
- * Delta Leland Chrome Dual Handle Faucets in Baths
- * 60" One Piece Fiberglass Tub/Shower with Anti-Scald Valves
- * Elongated Water Closets, Water Saver
- * 8" Deep, Double Bowl S/S Sink and Gooseneck Faucet with Pull-Down Spray in Kitchen
- k Ice Maker Hook-Up (Recessed Box for On-Site Appliance)
- * 2-in-1 Shower Hand Spray in Master Bath

Electrical

- ★ 200 AMP Main Service Panel with 40 Breaker Spaces
- * Smoke Detectors and Carbon Monoxide Detectors (Per Code)
- * Fan/Light Combination in All Baths
- ★ 30" Kitchen Range Hood; Vented to Exterior
- ★ Bedrooms Have One Switched Receptacle
- Brushed Nickel Ceiling Lights in Hall, Laundry, Kitchen, Dining Room, Foyer, and Walk In Closets
- * Recessed Can Light Over Kitchen Sink with Separate Switch
- * Two Pendant Lights Above Islands and Peninsulas (Per Plan)
- ★ Wireless Door Chimes (1 in Front and 1 in Rear)
- * (2) RG-6 TV and (2) Cat-5 Phone Jacks
- ★ Wired for Electric Range (Per Plan)

Warranty

* All Icon Legacy Custom Modular Homes Come with a 10 Year Structural Warranty

Additional Specs For:

Raised Ranch

- * Recessed Entry (Per Standard Floor Plan)
- * 4-Way Switch for Foyer Area
- Landing with Floor Vinyl and Stairs Up to Living Area with Carpet to Match Living Room (All Shipped Loose)

Cape

- * 8" Mating Walls @ 16" O.C. with Sheathing (First Floor)
- * Rafter Roof with 12/12 Pitch @ 16" O.C. and 5/8" OSB Floor Decking
- (2) Gable End Windows with Style and Type to Match First Floor
- * 30" Pre-hung Interior Door with 24' of Interior Walls
- * Plumbing and Electric Stubbed up for Future on-site Bath and Living Area

Two Story

- * 8" Mating Walls @ 16" O.C. with Sheathing (First Floor)
- Insulation Installed Around Perimeter Between Floor and Ceiling
- * Plumbing Supply Lines Run on Second Floor to Drop Area
- * All Siding for Second Story Shipped Loose
- Products may change at any time, with or without notice, depending on availability from the manufacturer and/or vendor or Icon Legacy Custom Modular Homes' decision to switch to a different product.
- * Revised 04/16/2013